



0223 Service Trenching

Document version: 2.0

Published date: 30/11/2022

Disclaimer: The information within this document once printed/exported will be classed as an uncontrolled copy. Its currency must be checked by visiting the EFSG/Technical Standards website prior to using the information for any purposes.

Table of contents

0223 Service Trenching.....0

 Table of contents.....1

 List of tables1

 List of figures1

 00 Design principles.....2

 0.01 Main considerations2

 Specification2

 01 General.....2

 02 Product2

 03 Execution.....2

 3.3 Excavating2

 04 Selections.....2

List of tables

No table of figures entries found.

List of figures

No table of figures entries found.

00 Design principles

0.01 Main considerations

It is a requirement to undertake the [00 PLANNING AND DESIGN/0001R - DESIGN REFERENCE](#) and [GLOSSARY OF TERMS](#) information into all aspects of design, detailing and delivery when developing the content here within. Clear demonstration of adherence to these requirements is part of the services and will be called upon at key points in the project and during at the discretion of the Department of Education (DoE).

Specification

01 General

As per current NATSPEC.

02 Product

As per current NATSPEC.

03 Execution

As per current NATSPEC except as follows:

3.3 Excavating

GUIDE NOTE: Delete subclause "Obstructions" nominated in NATSPEC, Building Professional Template / Worksection and include the following:

Obstructions

Cut back roots encountered in trenches to the edge of trench or a distance not less than 600 mm clear of the relevant service, and as specified in [02 SITE URBAN AND OPEN SPACES/0221 SITE PREPARATION](#). Remove such other obstructions including roots, stumps, boulders and the like which may, interfere with the proper functioning of the service.

04 Selections

As per current NATSPEC.