



0612 Cementitious Toppings

Document version: 2.0

Published date: 30/11/2022

Disclaimer: The information within this document once printed/exported will be classed as an uncontrolled copy. Its currency must be checked by visiting the EFSG/Technical Standards website prior to using the information for any purposes.

Table of contents

0612 Cementitious Toppings 0

 Table of contents.....1

 List of tables1

 List of figures1

 00 Design principles.....2

 0.01 Main considerations2

 0.02 Circulation areas2

 0.03 External steps & stairs2

 Specification2

 01 General.....2

 02 Product2

 03 Execution.....2

 3.3 Surface Finishes.....3

 04 Selections.....3

List of tables

Version history.....**Error! Bookmark not defined.**

List of figures

No table of figures entries found.

00 Design principles

0.01 Main considerations

It is a requirement to undertake the [PLANNING AND DESIGN/ 0001R - DESIGN REFERENCE](#) and [GLOSSARY OF TERMS](#) information into all aspects of design, detailing and delivery when developing the content here within. Clear demonstration of adherence to these requirements is part of the services and will be called upon at key points in the project and during at the discretion of the Department of Education (DoE).

0.02 Circulation areas

Enclosed circulation area finishes are to match the majority of spaces served by that area.

Unenclosed circulation floor finishes will generally be broomed concrete.

0.03 External steps & stairs

Non-slip granolithic.

Delineate all step nosing's in a non-slip, long lasting/wearing, contrasting tread colour to Building Code of Australia/National Construction Code (BCA/NCC) requirements.

Specification

01 General

As per current NATSPEC.

02 Product

As per current NATSPEC.

03 Execution

As per current NATSPEC except as follows:

GUIDE NOTE: Delete the clause "slip resistant treatment to stair treads" in the NATSPEC Building Template and replace with the following clause:

3.3 Surface Finishes

Slip Resistant treatment to stair treads

Slip resistant treatment: Provide colour-contrasting, non-slip proprietary nosing, in accordance with AS1428.1, fixed to each tread.

04 Selections

As per current NATSPEC